



INTÉRIOR FINISH  
 FURRING 1"X3" HOR. 16" c/c  
 GYPSUM 1/2" MIN.  
 VAPOR BARRIER  
 INSULATION  
 SILL GASKET

SIDING  
 FRAMING STUD 2" X 6" @ 16" C/C  
 FIBRE BOARD SHEATING 7/16"  
 AIR BARRIER  
 FURRING 1" X 3" @ 16" C/C  
 VAPOR BARRIER  
 INSULATION  
 SHEET METAL FLASHING

SILL GASKET  
 ANCHOR BOLT 4' C/C  
 1/2" X 8" LG.  
 REINFORCING STEEL  
 HORIZONTAL AND VERTICAL  
 AS PER CODES  
 AND REGULATIONS  
 OR BY STRUCTURAL ENGINEER

POLYCRETE  
 BIG BLOCK 1600-6"  
 MASONRY  
 143 mm (5-5/8") OF CONCRETE  
 ACRYLIQUE PARGING  
 OR EQUIVALENT

INTÉRIOR FINISH  
 FURRING 1"X3" VER. 16" c/c  
 GYPSUM 1/2" MIN.  
 POLYCRETE BIG BLOCK 1600-6"  
 RÉGULAR 24" X 96"

BACKFILL SOIL  
 SLOPE OF 2% MIN.

4" (100mm) CONCRETE SLAB  
 WIREMESH OR  
 STRUCTURAL FIBER  
 2 1/2" (64) INSULATION PANEL

WATERPROOF MEMBRANE  
 OR EQUIVALENT  
 NOTE: Sheathing 7/16" (optional)  
 as a membrane protection

CONTINUOUS CONCRETE FOOTING  
 20 mPa - 14 mm AGGREGATES  
 REINFORCING STEEL:  
 3 CONTINUOUS 10M  
 15M TRANSVERSAL 16" C/C  
 DOWEL L 15M STAGGERED 16" C/C

GEOTEXTILE MEMBRANE  
 CRUSHED STONE 3/4"  
 PERFORATED DRAIN



**TITLE:**  
 Big Block 1600-6" masonry 143 mm (5-5/8") of concrete  
 for wood frame construction.

**DRAWING NO:**  
 BB-06-S2000-EN

**DATE**  
 2011-05-15

**DISCLAIMER NOTICE**

SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH  
 LOCAL CODES IS THE RESPONSABILITY OF THE DESIGNER.

**DRAWING BY:**  
 AG

**REV. NO:**

**REV. DATE:**