

1

2

3

4

F

FACTORY FINISHED CONTINUOUS METAL COPING FASTENED TO BLOCKING @ 12" O.C. PER MANUF REQUIRMENTS

PRESSURE TREATED WOOD BLOCKING ANCHORED TO CONCRETE

FACTORY FINISHED METAL FLASHING

1/2" EXTERIOR SHEATHING

PVC/KEE FLASHING MEMBRANE, HOT-AIR WELDED

E

SELF ADHERING RUBBERIZED ASPHALT SHEET MEMBRANE LAPPING ROOF UNDERLAYMENT 3'-0", WRAPPING UP WALL AND OVER CONCRETE

PVC/KEE MEMBRANE, HOT-AIR WELDED OVER SELF ADHERING RUBBERIZED ASPHALT SHEET MEMBRANE, RIGID INSULATION (R-36), METAL DECK AND STEEL ROOF TRUSSES. SEE STRUCTURAL DRAWINGS FOR DETAILS

STRUCTURAL BENT PLATE

PRESSURE TREATED WOOD NAILERS SECURED TO METAL DECKING

D

5/8" GYPSUM WALL BOARD TO COVER RIGID INSULATION

C

4" MIN.

8" MIN.

EXTERIOR INSULATION FINISHING SYSTEM (EIFS) OVER ICF WALL SYSTEM (SEE SPEC 07 24 00)

CONTINUOUS SEALANT

FACTORY FINISHED METAL FLASHING

FACTORY FINISHED METAL COUNTER FLASHING

PRESSURE TREATED WOOD BLOCKING ANCHORED TO CONCRETE

STANDING SEAM METAL ROOF OVER SELF ADHERING RUBBERIZED ASPHALT SHEET MEMBRANE, RIGID INSULATION (R-12), METAL DECK AND STEEL ROOF TRUSSES. SEE STRUCTURAL DRAWINGS FOR DETAILS

FACTORY FINISHED SOLID METAL SOFFIT PANEL OVER 3/8" HAT CHANNELS @ 24" O.C.

EXTERIOR INSULATION FINISHING SYSTEM (EIFS) OVER ICF WALL SYSTEM (SEE SPEC 07 24 00)

C1 PARAPET DETAIL

1 1/2" = 1'-0"

0 1/2' 1' 1 1/2'